



BIOSCRYPT  
ENTERPRISE ACCESS SOLUTIONS

L-1 Identity Solutions —  
Delivering Expertise in  
Enterprise Access Control

Invest in solutions from the industry  
leader in biometric access control.  
Organizations that cannot afford to  
compromise on security rely on us.

We are a pioneer in the use of  
biometrics for access control and are  
dedicated to protecting government  
sites and businesses around the world.

## L-1 Fingerprint Reader Solutions

# Bioscrypt V-Enclosure™

### Protect your L-1 Fingerprint Reader from the Elements

Protect your L-1 fingerprint reader from extreme weather conditions with the V-Enclosure. The enclosure is available with a solid front panel or transparent window front covering to provide two different aesthetics to protect your reader from heat, cold, rain and blowing sand or dirt.

#### Durable Construction

- Fiberglass construction protects the reader from heat, cold, rain and blowing sand or dirt
- Transparent front window for easy visibility of reader inside or solid front option available

#### Simple Installation

- Mounting plate included for smooth surfaces (e.g. wood, metal)
- Multiple models to accommodate different Bioscrypt fingerprint readers, including V-Station, V-Smart, V-Pass FX and V-Prox

#### Heating Option

- Broad temperature operating range from 58° – 302°F (50° – 150°C)
- Heater option available to keep reader at ambient temperature of approximately 75°F (24°C)



*Window option shown with  
V-Station reader featured.*

*Reader sold separately.*

## SPECIFICATIONS

<b>DIMENSIONS</b>	Length 11.6" (295 mm) Width 9.4" (238 mm) Depth 5.5" / 7.4" with protective cable gland (140 mm / 187 mm)
<b>WEIGHT</b>	5.8 pounds (2.6 kg)
<b>HEATING OPTIONS</b>	The optional integrated heater is specifically designed to keep the reader at an ambient temperature of approximately 75°F (24°C)
<b>OPERATING TEMPERATURE</b>	58° – 302°F (50° – 150°C) 0 - 90% relative humidity; non-condensing
<b>POWER REQUIREMENTS</b>	12 VDC (fingerprint reader unit requires separate power supply) With heater: 7.6 amps @ 12 VDC

## ORDERING INFORMATION

### V-PASS FX AND V-PROX MODELS

Base unit	V-ENC-R
Base unit with window	V-ENC-W-R
Base unit with heat	V-ENC-Ht-R
Base unit with window and heat	V-ENC-W-Ht-R

### V-SMART MODELS

Base unit	VT-ENC-R
Base unit with window	VT-ENC-W-R
Base unit with heat	VT-ENC-Ht-R
Base unit with window and heat	VT-ENC-W-Ht-R

### V-STATION MODELS

Base unit	VN-ENC-R
Base unit with window	VN-ENC-W-R
Base unit with heat	VN-ENC-Ht-R
Base unit with window and heat	VN-ENC-W-Ht-R

All models require customer-supplied power supply

Fingerprint reader units require separate power supply

Fingerprint reader sold separately



BIOSCRYPT  
ENTERPRISE ACCESS SOLUTIONS

## The L-1 Enterprise Access Division



### Americas

Sales-EnterpriseAccess@L1ID.com  
800 444 0496 • 905 940 7490

### International

Sales-Intl-EnterpriseAccess@L1ID.com  
+41 22 849 1051

### Offices

Canada • United States • Switzerland