



BIOSCRYPT  
ENTERPRISE ACCESS SOLUTIONS



# 4G V-Flex WR

## Features at a glance

- IP 65 Rated for Outdoor Environments
- Built in Hood and Specialized Components for Weather Resistant Protection
- Large Template Storage Capacity (10,000 in 1:N; 500,000 in 1:1)
- Optional Integrated Card Readers (Prox, iClass or MIFARE/DESFire)
- Backwards Compatible
- Remote Device Management
- IP Connectivity (LAN, WAN, POE)
- Easy Administration with SecureAdmin™
- Flush or Recess Mounted
- Standalone Door Access Control (SDAC) Capabilities

## Ideal Deployment Locations

- Temperature range between -5°F to 140°F (-20°C to 60°C).
- The device is sealed and designed to withstand water, however for optimal biometric performance the sensor and finger should be dry.
- For convenience, install in an outdoor area that offers some degree of protection from direct elements, such as under a building overhang. (see image at top)

If you require a device that offers additional outdoor capabilities please see our 4G V-Station Extreme™ device.

## Power and Flexibility in a Weather Resistant Compact Design

Not every solution requires extreme weather performance. When you need a compact device for use in moderate outdoor climates with powerful biometric capabilities, the V-Flex 4G WR is the right solution for you. The Weather Resistant (WR) models have specialized components and a built in hood that offers protection against certain outdoor elements.



### Prepare for the Demands of Today and the Future with a Scalable Platform

Quick throughput, deployment flexibility, and the ability for the system to expand over time address today's demands and are drivers for future requirements.

- Ensure employees gain fast access with over 6,000 templates searched per second.
- Accommodate enterprise installs with storage of 500,000 templates for 1:1 verification.
- Eliminate the need for cards and PINs - store 10,000 templates for 1:N.

### Meet Challenging Security Requirements

A full range of options are available for different security requirements.

- Remove install constraints with configurable options for multi-factor authentication.
- Reduce cost and complexity with built-in door relay and controls.
- Add safety and security measures for employees with the duress finger option.

### Reduce Maintenance Costs

Save time and drive down the cost of ownership with a communication-ready connected smart device, containing new installation and maintenance capabilities.

- Leverage the latest communication standards - Full Ethernet, POE, RS485.
- Take full advantage of IP connectivity for remote device management.

### Leverage Existing Infrastructure

Backwards compatible and purpose built to work with security industry technologies.

- Eliminate the need for re-enrollment with support for Bioscrypt legacy template formats.
- Leverage existing Bioscrypt integrated systems - works with existing BioSDK integrations with PAC partner applications.

# 4G V-Flex WR™

## Product Specifications

|                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                          |
|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| Dimensions                              | Recessed Mounted:<br>Height 7.52" (191 mm)<br>Width 4.15" (105 mm)<br>Depth 1.89" (48 mm)                                                                                                                                                                                                                                                                                                                                                                                                                 | Flushed Mounted:<br>Height 7.52" (191 mm)<br>Width 4.15" (105 mm)<br>Depth 2.56" (65 mm) |
| Communications                          | Networking Options: LAN, WAN, RS485<br>PC Connection: USB, RS232                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                          |
| External Media                          | USB memory                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                          |
| Input / Outputs                         | Wiegand (Customizable format up to 512 bits)<br>3 General Purpose Inputs<br>3 General Purpose Outputs (Extendable to 6 outputs)                                                                                                                                                                                                                                                                                                                                                                           |                                                                                          |
| Fingerprint Sensor                      | Secugen Optical (500 dpi)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                          |
| Internal Card Reader Options            | V-Flex 4G (Prox) – integrated reader for proximity cards<br>V-Flex 4G (Smart) – Integrated card reader for iClass or MIFARE/DESfire cards                                                                                                                                                                                                                                                                                                                                                                 |                                                                                          |
| Template Storage Capacity               | 500,000 per unit for 1:1 verification<br>10,000 per unit in 1:N identification (Standard)                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                          |
| Transaction Log Capacity                | 1 Million transaction logs stored on device                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                          |
| Authentication Modes                    | 4G V-Flex WR (Base) <ul style="list-style-type: none"> <li>• Finger-only single-factor authentication</li> <li>• Card or PIN + Finger (with an external reader)</li> </ul> 4G V-Flex WR (Prox) <ul style="list-style-type: none"> <li>• Prox Card + Finger</li> <li>• Prox Card Only</li> <li>• Finger Only</li> </ul> 4G V-Flex WR (Smart Card) <ul style="list-style-type: none"> <li>• Smart Card + Finger</li> <li>• Smart Card + Finger + PIN</li> <li>• Card Only</li> <li>• Finger Only</li> </ul> |                                                                                          |
| Template Support                        | Bioscrypt Pattern and Minutia                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                          |
| Power over Ethernet (POE)               | Standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                          |
| Voltage                                 | 12 - 24V DC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                          |
| Current Draw                            | 500 mA, 0.5 amps @ 12VDC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                          |
| Power Indicator                         | LED indicator (Blue)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                          |
| Integrated Door Relay                   | Deadbolt, electromagnetic (EM) lock, door strike, automatic door                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                          |
| Mounting                                | Recessed or Flush mount                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                          |
| Operating Temperature                   | -5° - 140°F (-20° - 60°C)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                          |
| Regulatory Approvals and Certifications | FCC, CE, R&TTE, RoHS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                          |
| Administration Software Options         | Works with SecureAdmin™ software or SecureSDK™                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                          |

### Device Models

|                        | 4G V-Flex WR (Base) | 4G V-Flex WR (Prox) | 4G V-Flex WR (iClass) | 4G V-Flex WR (MiFare/DESFire) |
|------------------------|---------------------|---------------------|-----------------------|-------------------------------|
| Secugen Optical Sensor | XFXS                | XFXSP               | XFXSH                 | XFXSG                         |

vFXWR.01.03.10

### About L-1 Identity Solutions Enterprise Access Division

With over 350,000 readers deployed in over 90 countries, the Enterprise Access Division of L-1 protects and secures identities and assets by helping customers address demanding access control and identity authentication requirements with innovative and reliable systems.

#### Our Advantage:

- One of the most established companies that specialize in biometric access control solutions.
- Market-tested and customer proven solutions that are interoperable, and designed to grow with you.
- Knowledgeable technical support team ready to help answer your questions and get you up and running.

### The L-1 Enterprise Access Division

#### Americas

Sales-EnterpriseAccess@L1ID.com  
 800 444 0496 • 905 940 7490

#### International

Sales-Intl-EnterpriseAccess@L1ID.com  
 +41 22 849 1051

#### Offices

Canada • United States • Switzerland

[www.L1ID.com/EnterpriseAccess](http://www.L1ID.com/EnterpriseAccess)

Copyright © 2009, L-1 Identity Solutions, Inc. All rights reserved. The trademarks identified herein are the trademarks or registered trademarks of L-1 Identity Solutions, Inc. or other third party.

Call or email us to [Schedule](#) an appointment today for a solution overview and demo.